



Rosebud[®]VC

VITAL SIGNS MONITOR



Specifications

Interfacing

Connectors: Network port
2 USB ports
Multifunctional port

Battery

Type: Rechargeable lithium ion
Run Time: Up to 8 hours when powered by a new full-charged battery at 77°F+41°F (25°C+5°C) with SpO2 and NIBP measurements at an interval of 15 minutes.

Charge Time

Monitor Power Off: Less than 5.5 hours to 90%; Less than 6.6 hours to 100%
Monitor Power On: Less than 10.5 hours to 90%; Less than 11.5 hours to 100%

Physical Dimensions

Monitor Size: 10.2" (H) x 6.9" (W) x 6.9" (D) 25.9 cm (H) x 17.5 cm (W) x 17.5 cm (D)
Monitor Weight: <5/5 lbs (<2.5kg) including battery

Environmental Conditions

Operating Temperature: 0°C to 40°C (SmarTemp™: 5°C to 40°C)
Operating Humidity: 15% to 95%, non-condensing
Barometric: 427.5 to 805.5 mmHg (57.0 to 107.4 kPa)


Power Requirements

100 to 240VAC, 0.9 to 0.5A, 50/60 Hz

Safety

Type of Protection: Meets the requirements of IEC 60601 series

Top




Front



Side



Top with Temperature



Front with Temperature



Side with Temperature



Rosie

WHERE TECHNOLOGY AND THE CARING TOUCH MEET
800.841.1109 | info@nurserosie.com | nurserosie.com